

## AMENDMENTS TO THE SPECIFICATION

Please replace the paragraph comprising lines 28-29 of page 17 through lines 1-11 of page 18 with the following replacement paragraph:

-- Figure 6 illustrates a view of rear end 44 of insert 10. Upper row 14 lead frames are at least about 0.1 inch above lower row 16 lead frames. When compared with the rear end of prior insert devices as shown in Figure 8, it can clearly be observed that the two frames 19-25 21 and 23 of upper row 14 are laterally offset with respect to the two frames 20 and 22 of lower row 16 while the prior insert frames are evenly spaced from each other. ~~Preferably, so that~~ the horizontal distance between lead frames 18 and 20 of the lower row 16 is preferably about 0.1 inches, the horizontal distance between frames 20 and 22 thereof is preferably about 0.05 inches, and the horizontal distance between frames 22 and 24 thereof is preferably about 0.2 inches. ~~Whereas,~~ the horizontal distance between frames 19 and 21 of the upper row 14 is preferably about 0.2 inches, the horizontal distance between frames 21 and 23 thereof is preferably about 0.05 inches, and the horizontal distance between frames 23 and 25 thereof is preferably about 0.1 inches. In contrast, the prior insert device exhibits the same horizontal distances between all lead frames of about 0.1 inches each. --